

AMENDMENT TO THE CLAIMS

1. (currently amended) An apparatus for use in an industrial process control or monitoring system, comprising:

a process device for coupling to an industrial process which includes a process transmitter or controller to monitor or control the industrial process and communicate;

a process coupling configured to couple the process device to a process which includes piping carrying a process fluid, the process coupling configured to receive vibrations from the process;

a vibration sensor configured to receive vibrations from the process which are transferred from the process through the process coupling and to sense vibrations and provide a sensed vibration signal ~~solely for use in performing diagnostics~~;

diagnostic circuitry located in the process device configured to receive the sensed vibration signal and responsively provide a diagnostic output related to a process disturbance or operation of a process component; and

wherein the process device includes a process variable sensor separate from the vibration sensor configured to sense a process variable; and

wherein the diagnostic comparison is based upon a comparison of an accumulation of sensed vibrations to a threshold.

2. (canceled)

3. (previously presented) The apparatus of claim 1 wherein the process device includes a control element separate from the vibration sensor configured to control operation of the process.

4. (original) The apparatus of claim 1 wherein the process device includes an input configured to receive a process signal.

5. (previously presented) The apparatus of claim 1 wherein the process device includes output circuitry including communication circuitry configured to couple to a two-wire process control loop.
6. (original) The apparatus of claim 1 wherein the vibrations are carried through process components.
7. (original) The apparatus of claim 1 wherein the vibration sensor comprises an accelerometer.
8. (original) The apparatus of claim 1 wherein the vibration sensor is configured to sense vibrations along one axis.
9. (original) The apparatus of claim 1 wherein the vibration sensor is configured to sense vibrations along more than one axis.
10. (original) The apparatus of claim 1 wherein the output from the diagnostic circuitry is transmitted on a process control loop.
11. (original) The apparatus of claim 1 wherein the diagnostic output is related to failure of a process component.
12. (original) The apparatus of claim 1 wherein the diagnostic output is related to degradation in performance of a process component.
13. (original) The apparatus of claim 1 wherein the diagnostic output is related to an impending failure of a process component.

14. (original) The apparatus of claim 1 wherein the diagnostic output is based upon a comparison of sensed vibrations to a base line level.
15. (previously presented) The apparatus of claim 14 wherein the base line level is determined based upon history of the process.
16. (cancelled)
17. (cancelled)
18. (original) The apparatus of claim 1 wherein the diagnostic output is based upon trends in the sensed vibrations.
19. (original) The apparatus of claim 1 wherein the diagnostic output is used to adjust a control algorithm.
20. (original) The apparatus of claim 1 wherein the diagnostic output is used to compensate a process variable measurement.
21. (original) The apparatus of claim 1 wherein the diagnostic output is based upon a frequency spectrum of the sensed vibrations.
22. (original) The apparatus of claim 1 wherein the diagnostic output is based upon rules.
23. (original) The apparatus of claim 1 wherein the diagnostic circuitry implements a neural network.

24. (original) The apparatus of claim 1 wherein the diagnostic circuitry implements fuzzy logic.

25. (original) The apparatus of claim 1 wherein the diagnostic output is based upon sensed spikes in the vibration signal.

26. (original) The apparatus of claim 1 wherein the diagnostic output is based upon a rolling average of the vibration signal.

27. (original) The apparatus of claim 1 wherein the vibration sensor is selected from a group of vibration sensors including of capacitive, electrodynamic, piezoelectric and Micro-Electro-Mechanical Systems (MEMS).

28. (original) The apparatus of claim 1 wherein the diagnostic output is correlated with process operation.

29. (original) The apparatus of claim 1 including a plurality of process devices configured to sense vibrations.

30. (original) The apparatus of claim 1 wherein the process device is completely powered from a process control loop.

31. (original) The apparatus of claim 1 wherein the process device is configured to couple to a process control loop selected from the group of process control loops consisting of two, three and four wire process control loops.

32. (currently amended) A method of monitoring operation of an industrial process control system, comprising:

physically coupling a process device using a process coupling to an industrial process which carries a process fluid in process piping and which includes process transmitters or controllers to monitor or control the industrial process which communicate;
receiving vibrations from the process through the process coupling;
sensing process vibrations with a vibration sensor in the process device, the vibrations received through the physical coupling and transferred from the process through the process coupling and to the vibration sensor ~~the sensed vibrations solely for use in performing diagnostics;~~
diagnosing operation of a process component or a process disturbance based upon the sensed vibrations; ~~and~~
sensing a process variable with a process variable sensor in the process device which is separate from the vibration sensor; and
wherein the diagnostic comparison is based upon a comparison of an accumulation of sensed vibrations to a threshold.

33. (canceled)

34. (previously presented) The method of claim 32 including controlling operation of the process with a control element which is separate from the vibration sensor.

35. (previously presented) The method of claim 32 including outputting diagnostic data on a two-wire process control loop.

36. (original) The method of claim 32 wherein the process vibrations are carried through process components.

37. (original) The method of claim 32 wherein sensing vibrations comprises sensing vibrations along one axis.

38. (original) The method of claim 32 wherein sensing vibrations comprises sensing vibrations along more than one axis.

39. (original) The method of claim 32 wherein the diagnosing is related to failure of a process component.

40. (original) The method of claim 32 wherein the diagnosing is related to an impending failure of a process component.

41. (original) The method of claim 32 wherein the diagnosing is based upon a comparing of sensed vibrations to a base line level.

42. (original) The method of claim 41 wherein the base line level is determined based upon history of the process.

43. (cancelled)

44. (cancelled)

45. (original) The method of claim 32 wherein the diagnosing is based upon trends in the sensed vibrations.

46. (original) The method of claim 32 including adjusting a control algorithm based upon the diagnosis.

47. (original) The method of claim 32 including compensating a process variable measurement based upon the diagnosing.

48. (original) The method of claim 32 wherein the diagnosing is based upon a frequency spectrum of the sensed vibrations.

49. (original) The method of claim 32 wherein the diagnosing is based upon rules.

50. (original) The method of claim 32 wherein the diagnosing is implemented in a neural network.

51. (original) The method of claim 32 wherein the diagnosing is implemented in fuzzy logic.

52. (original) The method of claim 32 wherein the diagnostic output is based upon sensed spikes in the vibration signal.

53. (original) The method of claim 32 wherein the diagnosing is based upon a rolling average of the vibration signal.

54. (original) The method of claim 32 including correlating the diagnosing with process operation.

55. (previously presented) The apparatus of claim 1 wherein the vibration sensor senses vibration in the process received through a mounting arrangement.

56. (previously presented) The apparatus of claim 1 wherein the vibration sensor senses vibration in the process received through a wiring system.